



## Descripción

- ▶ EPI de categoría II.
- ▶ Guante sin costuras en una sola pieza.
- ▶ Dorso y puño de algodón y poliéster.
- ▶ Recubrimiento de látex con acabado rugoso que facilita el agarre. Altas prestaciones a un precio económico.
- ▶ Se adapta a la mano siguiendo su contorno.
- ▶ Puño elástico que se ciñe en la muñeca.
- ▶ El dorso fresco permite mantener la mano ventilada.
- ▶ Alto nivel de dexteridad (nivel 5)



**LÁTEX  
ACABADO  
RUGOSO  
EN PALMA**

## Materiales

- ▶ Dorso y puño en algodón y poliéster
- ▶ Ribete de nylon
- ▶ Palma y uñeros de látex



### RESISTENCIAS (EN388)



2142X

ABRASIÓN	2
CORTE	1
RASGADO	4
PERFORACIÓN	2
CORTE TDM	X

### CARACTERÍSTICAS TÉCNICAS



Se sirve en bolsa individual para colgar

### TALLAS

7 (S) 8 (M) 9 (L) 10 (XL)

### DEXTERIDAD

NIVEL 5

### LONGITUD

26 cm

### ESPESOR

0,25 mm

### EMBALAJE

Bolsas de 12 pares (unidad mínima de venta)  
Cajas de 120 pares  
Se sirve con bolsa individual para colgar

## Aplicaciones

- ▶ Construcción, agricultura, manipulación, etc

## STANDARDS

- ▶ **EN420** (requisitos generales)
- ▶ **EN388** (resistencias mecánicas)



[WWW.SAFETOP.NET](http://WWW.SAFETOP.NET)





## Description

- Category II PPE.
- Seamless glove in one piece.
- Cotton and polyester back and cuff.
- Latex coating with a rough finish for easy grip. High performance at an economical price.
- It adapts to the hand following its contours.
- Elasticated cuff that fits snugly around the wrist.
- The cool back of the hand keeps the hand ventilated.
- High level of dexterity (level 5)



**LATEX  
FINISH  
ROUGH  
IN PALM**

## Materials

- Cotton and polyester back and cuffs
- Nylon piping
- Latex palm and cuffs



### RESISTANCES (EN388)



2142X

ABRASION	2
CUT	1
RIPPING	4
DRILLING	2
CUTTING TDM X	

### TECHNICAL CHARACTERISTICS



Supplied in an individual individual for hanging

### SIZES

7 (S) 8 (M) 9 (L) 10 (XL)

### DEXTERITY

NIVEL 5

### LENGTH

26 cm

### THICKNESS

0,25 mm

### PACKAGING

Bags of 12 pairs (minimum unit of sale)  
Boxes of 120 pairs  
Supplied with individual hanging bag

## Applications

- Construction, agriculture, handling, etc.

## STANDARDS

- EN420 (general requirements)
- EN388 (mechanical resistances)



[WWW.SAFETOP.NET](http://WWW.SAFETOP.NET)

